



Vitacci Pentora IRide 125 ATV

[Read More](#)

SKU: PENT-IRIDE

Categories: [Vitacci](#)

Product Description

Vitacci Pentora IRide 125 ATV

Due to high demand this time of year availability is limited. Please confirm availability with us.

ITEMS	SPEC
Engine Model	ZS154FMI-5
Engine Type	Single cylinder, 4-stroke, air-cooled, camshaft upward, with balance shaft, 10° tilted
Displacement	123.67 ml
Max. Power	6.3 kW (±10%) / 7500 rpm (±5%)
Max. Torque	8.8 N·m (±10%) / 5500 rpm (±5%)
Compression Ratio	9.0:1
Bore × Stroke	54 × 54 mm
Ignition Method	CDI
Lubrication Method	Pressure and Splash
Lubricating Oil	15W/40-SE (-10 to 40°C), HQB-10 (< -10°C)
Starting Method	Electric start
Clutch Method	Automatic Wet Multi-Plate
Gearshift Method	Constant mesh, two-stage transmission, Automatic (Forward, Neutral, Reverse)
Transmission	Chain
Spark Plug	A7RTC

ATV SIZE |

Overall Size (L × W × H) | 1430 × 965 × 950 mm

Wheelbase | 970 ± 20 mm

Wheel Track | Front: 750 ± 15 mm / Rear: 760 ± 15 mm

Seat Height | 700 ± 15 mm

Ground Clearance | 180 mm

Minimum Turning Circle Radius | 2500 ± 500 mm

Height (Foot Pedal to Seat) | 445 ± 15 mm

Sprocket | Front: 428-14 / Rear: 428-42

Brake | Front & Rear Disc Brake

Brake Method | Hand brake (Front & Rear)

Rim | Front & Rear: 8 inch

Tire | Front: 18 × 7-8 / Rear: 18 × 9-8

Front Suspension | Oil damper, 270 mm

Rear Suspension | Oil damper, 285 mm

Lighting |

Front Light | 2 × 12V / 25W

Tail Light | LED

Turning Light | -

Carburetor | PZ19

Fuel Tank Capacity | 7 L

Frame | Double beam welded frame

Rear Swing Arm | Tube and plate structure

Max. Loading | 82 kg

Net Weight (N.W.) | 109 kg

Gross Weight (G.W.) | 131 kg

Packing | Steel frame + carton

Packing Size | 1310 × 850 × 650 mm

Loading Quantity | 92 pcs / 40HQ

Available Colors

- Black
 - Blue
 - Green
 - White
-